

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (currently amended) A network element residing in an optical transport network, comprising:

an optical transport line terminating at the network element, the optical transport line operable to carry an optical system signal therein;

a demultiplexing component connected to the optical transport line, the demultiplexing component operable to receive the optical system signal and separate the optical system signal into a plurality of intermediate optical signals; and

a plurality of optical fibers connected to the demultiplexing component, and
a plurality of management signal sources interposed between the demultiplexing component and the plurality of optical fibers, where each of the management signal sources introduces an optical management signal into a corresponding optical fiber, such that each of the optical fibers carries ~~operable to carry~~ an optical management signal and one of the plurality of intermediate optical signals therein; the optical management signal being transmitted at a wavelength different than the wavelength range used to transmit the intermediate optical signal.

2. (original) The network element of Claim 1 wherein the optical management signal is transmitted at a wavelength that is spectrally separated from the transmission wavelength range for the plurality of intermediate optical signals.

3. (original) The network element of Claim 2 wherein the plurality of intermediate optical signals are transmitted at a wavelength in the range of 1520nm to 1610nm and each of the optical management signals are transmitted at substantially 1310nm.

4. (cancelled)

5. (original) The network element of Claim 1 wherein the optical management signal is transmitted in the absence of the intermediate optical signal.

6. (cancelled)

7. (currently amended) The network element of Claim 1 6 wherein at least one of the management signal sources includes a laser source operable to generate an optical management signal, and a signal combiner operable to combine the optical management signal from the laser source with the intermediate optical signal traversing through the corresponding optical fiber.

8. (original) The network element of Claim 1 further comprising a plurality of management signal receivers connected to the plurality of optical fibers, each of the management signal receivers operable to receive and separate the optical management signal from the intermediate optical signal traversing through the corresponding optical fiber.

9. (currently amended) A method for managing an optical transport network, comprising:

terminating an optical transport line at a network element residing in the optical transport network, the optical transport line operable to carry an optical system signal and the optical system signal having a plurality of optical data signals embodied therein;

routing the plurality of optical data signals amongst a plurality of optical fibers associated with the network element; and

defining an optical management channel for each of the plurality of optical fibers by interposing a management signal source between the optical transport line and each of the plurality of optical fibers; and

transmitting an optical management signal from each of the management signal sources over a corresponding optical fibers, such that each optical fiber carries an optical data signal and an optical management signal ~~the optical management channel operable to carry an optical management signal therein.~~

10. (original) The method of Claim 9 further comprising the step of transmitting a first optical management signal over at least one of the optical management channels, the first optical management signal transmitted at a wavelength different than the wavelength range used to transmit an optical data signal through the corresponding optical fiber.

11. (original) The method of Claim 10 wherein the step of transmitting a first optical management signal further comprises selecting a wavelength that is spectrally separated from the wavelength range used to transmit the optical data signal.

12. (original) The method of Claim 11 wherein the first optical management signal is transmitted at substantially 1310nm and the optical data signal is transmitted at a wavelength in the range of 1520nm to 1610nm.

13. -18. (cancelled)